







Designed to minimize seed loss without sacrificing speed, the Fantini G03 is tailor-made for an unprecedented harvest experience. Specially designed collecting pans and a high capacity auger retain seeds and maximize crop flow. Available in models from four to 18 rows, the G03 easily adapts to any combine.

Thanks to a solid one-piece frame and tubular steel construction, the G03 is built to withstand the harshest field conditions. Simple, effective features including a one-piece row unit, transmission and PTO require minimal maintenance, yet can be easily repaired.







Additional Features and Accessories

- Row Unit Oil Bath Gears: High-tech hardened steel gears lubricated in an oil bath for exceptional durability and longevity.
- Easily Adjustable Row Unit Chain Tension
- Adjustable Feeder Arm: Moves stalks towards the auger.
- Adjustable Divider Points: Ensure maximum efficiency in down crops, thereby reducing crop loss. They also fold back for convenient transport.
- **Side Guard Height:** Optimized to minimize crop loss and prevent sunflower heads from falling outside the header.
- Auger and Row Unit Transmission System: Allows the operating speed of the auger or row units to be changed by utilizing different sprockets. These can be easily changed in the field.





G03 SPECIFICATIONS

MODEL	NUMBER OF ROWS*	INTER-ROW DISTANCE**	
	From 4 to 16	30 in.	
Rigid G03	From 6 to 16	22 in.	
	From 6 to 18	20 in.	

GP SPECIFICATIONS

MODEL	EFFECTIVE CUT	WIDTH	DEPTH	WEIGHT	
GP	31.5 feet	32.2 feet	8.3 feet	6,922 lbs	

*Different number of rows available upon request **Different row spacing available upon request







15526 90th St. NE Drayton, ND 58225 Phone: 701-454-3875

Email: help@hamiltonsystemsinc.com

See more Fantini unrivaled solutions:



🚹 🌇 fantini-na.com